

CLAIM AMENDMENTS

1 - 17. (canceled)

1 18. (new) In a motor vehicle, the combination
2 comprising:

3 a wall formed with a recess;

4 a hand tool adapted to fit with the recess and formed
5 with a throughgoing hole; and

6 latch means for releasably securing the tool in the
7 recess, whereby for use the hand tool can be grasped through the
8 hole and freed from the recess.

1 19. (new) The combination defined in claim 18 wherein
2 the hand tool is a ice scraper, screw driver, or bottle opener.

1 20. (new) The combination defined in claim 18 wherein
2 the vehicle has a center console forming the wall.

1 21. (new) The combination defined in claim 18 wherein
2 the latch means includes a magnet.

1 22. (new) The combination defined in claim 18 wherein
2 the latch means includes elastically deformable interfitting
3 formations on the tool and on the wall at an edge of the recess.

1 23. (new) The combination defined in claim 18 wherein
2 the throughgoing hole is at least as large as a standard beverage
3 can, whereby the tool can form part of a cup holder.

1 24. (new) The combination defined in claim 23 wherein
2 the opening is generally circular and has elastically deformable
3 lips adapted to grip a standard beverage can fitted in the hole.

1 25. (new) The combination defined in claim 24 wherein
2 the hole is at least partially of larger diameter than the standard
3 beverage can.

1 26. (new) The combination defined in claim 18 wherein
2 the tool is provided with a hard edge suitable for use as a
3 scraper.

1 27. (new) The combination defined in claim 18 wherein
2 the tool is elongated and has long sides formed with cutouts
3 facilitating gripping of the tool.

1 28. (new) The combination defined in claim 18 wherein
2 the tool is formed with a seat shaped to releasably retain a coin.

1 29. (new) The combination defined in claim 18 wherein
2 the tool is formed of a pair of similarly shaped secured-together
3 elements.

1 30. (new) The combination defined in claim 29 wherein
2 the tool includes a scraper blade fastened between and projecting
3 at an end from between the elements.

1 31. (new) The combination defined in claim 29, further
2 comprising
3 a light source fixed on the tool; and
4 a battery between the elements connectable to the source.